

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-8. (Canceled)

9. (Currently Amended) A plasma display device comprising:

a plasma display panel (PDP) having scan electrodes and sustain electrodes to form a plurality of electrode pairs; and

a first driving circuit ~~that initializes discharge cells by applying~~ configured to successively apply a first signal ~~having an initialing pulse and a second signal~~ to the scan electrodes ~~during a reset before an address~~ period of at least one sub-field,

wherein the first signal comprises an initialing pulse ~~increasing rising~~ to a first maximum voltage value, ~~wherein the first signal further has and~~ a first decreasing pulse ~~provided after the initialing pulse during the reset period of the at least one sub-field~~ falling to a first minimum voltage value, and[[;]]

~~wherein the first driving circuit applies a second signal having an enhancing pulse to the scan electrodes after applying the first signal in the reset period and before an address period of the at least one sub-field, wherein the second signal further has a second decreasing pulse provided after the enhancing pulse in the at least one sub-field, the enhancing pulse increasing to a second maximum voltage value less than the first maximum voltage value;~~

~~wherein the first decreasing pulse is provided until a voltage provided to the scan electrodes reaches a first voltage value, and the second decreasing pulse is provided until the voltage provided to the scan electrodes reaches a second voltage value, wherein the first voltage value is different than the second voltage value, and wherein a ground voltage is applied to the sustain electrodes when the enhancing pulse is applied to the scan electrodes~~

the second signal comprises an enhancing pulse rising to a second maximum voltage value less than the first maximum voltage value and a second decreasing pulse falling to a second minimum voltage value greater than the first minimum voltage value.

10. (Previously Presented) The plasma display device as set forth in claim 9, wherein the second maximum voltage value is lower than a sustain voltage applied to the scan electrodes or applied to the sustain electrodes in a sustain period of the at least one sub-field.

11. (Previously Presented) The plasma display device as set forth in claim 9, wherein a difference between the first maximum voltage value and the second maximum voltage value is substantially the same as a sustain voltage applied to the scan electrodes or the sustain electrodes in a sustain period of the at least one sub-field.

12. (Previously Presented) The plasma display device as set forth in claim 9, wherein a slope of the initialing pulse is substantially the same as a slope of the enhancing pulse.

13. (Currently Amended) The plasma display device as set forth in claim 9, wherein a ground voltage is applied to the sustain electrodes when the second ~~decreasing pulse signal~~ is applied to the scan electrodes.

14-17. (Canceled)

18. (Previously Presented) The plasma display device as set forth in claim 9, wherein a voltage substantially similar to a sustain voltage provided to the scan electrodes or to the sustain electrodes during a sustain period is provided to the sustain electrodes when the first decreasing pulse is applied to the scan electrodes.

19. (Currently Amended) A method of driving a plasma display panel based on a plurality of sub-fields, the plasma display panel having a plurality of discharge cells, and each of the cells having a scan electrode and a sustain electrode, the method comprising:

providing a first signal including an initialing pulse followed by a first decreasing pulse to the scan electrode during an initialization period of at least one sub-field;

providing successively a second signal including an enhancing pulse followed by a second decreasing pulse to the scan electrode after providing the first signal ~~and during the at least one sub-field~~, wherein a lowest voltage of the first decreasing pulse is less than a lowest voltage of the second decreasing pulse, ~~wherein a ground voltage is provided to the sustain electrode when the second signal is provided to the scan electrode;~~

providing a scan signal to the scan electrode during an address period of the at least one sub-field, the scan signal being provided after the second signal in the at least one sub-field;

providing at least one sustain signal to at least one of the scan electrode or the sustain electrode during a sustain period of the at least one sub-field,

wherein the initialing pulse of the first signal has a first peak voltage value, and the enhancing pulse of the second signal has a second peak voltage value, and wherein the first peak voltage value is greater than the second peak voltage value.

20-23. (Canceled)

24. (Previously Presented) The method of claim 19, wherein a sustain voltage is provided to the sustain electrode when the first signal is provided to the scan electrode.

25. (Canceled)

26. (New) The plasma display device as set forth in claim 9, wherein the second minimum voltage value is a voltage between a ground voltage and the first minimum voltage value.

27. (New) The plasma display device as set forth in claim 9, wherein the second decreasing pulse directly falls from the second maximum voltage value to the second minimum voltage value.